

SPECIFICATIONS

COIL SPRINGS

Spring Number	Bar Dia. mm	Free Height mm		Number Of Coils	Coil Weight Kg	Spring Rate	
		A	B			lbf/in	N/mm
OME875	18	440	440	10	8.7	240	42
OME876	14	390	375	8.5	3.7	200	35
OME880	16	365	365	10.2	4.7	500	88
OME881	16	375	375	10.2	4.7	500	88
OME882	16	395	395	10.2	4.7	500	88
OME883	17	375	375	10.6	5.7	590	103
OME884	17	385	385	10.6	5.7	590	103
OME885	17	395	395	10.6	5.7	590	103
OME886	17	365	365	10.65	5.7	590	103
OME890	15	435	425	10.2	5.7	190	33
OME891	16	420	410	10	6.4	210	37
OME892	18	400	390	10	8.1	380	68
OME895	17	390	390	6.75	5.6	260	45.5
OME895E	17	375	375	6.75	5.5	260	45.5
OME896	18	390	390	6.75	6.4	318	55.7
OME897	19	390	390	6.75	7.2	387	67.8
OME900	16	405	395	7.75	5.8	180	31.5
OME901	17	395	385	7.5	6.3	220	38.5
OME902	18	340	340	8.35	5.4	650	113.8
OME903	16	380	380	7.3	5.3	210	36.8
OME904	15	410	410	6.8	4.4	170	29.8
OME905	17	313	313	6	4.7	360	63
OME907	17	370	370	5.25	5.2	213	37.3
OME908	16	295	295	7.25	4.5	368	64.4
OME910	17	400	390	7.5	7.0	150-260	26-45.5
OME911	16	400	390	7.5	7.0	140-230	24.5-40
OME912	15	420	420	10.8	5.6	180-300	31.5-52.5
OME913	15	390	390	9.3	4.8	180-300	31.5-52.5
OME914	18	330	330	8.2	5.0	650	114
OME915	18	345	345	8.2	5.5	650	113.8
OME917	21	350	340	7.25	8.6	700-900	122-157
OME918	22	330	320	7.25	9.5	860-1000	150-175
OME919	15	430	430	10.8	5.7	200-280	35-49
OME920	14	430	430	8	3.6	190	33
OME921	16	385	385	6.8	5.3	200	35
OME922	15	360	360	7.5	4.7	140	24
OME923	16	395	395	6.8	5.3	200	35
OME924	19	345	345	8.2	6.2	790	138
OME925	16	385	385	10.8	5.4	375	65.7
OME926	16	392	392	10.8	5.4	375	65.7
OME927	16	394	394	10.3	5.2	400	70
OME928	16	410	410	6.8	5	200	35
OME929	16	420	420	10.8	6.6	240-300	42-52.5
OME930	14	475	465	9.8	3.9	160	28
OME931	14	510	500	11.9	5.1	140	24.5
OME932	14	480	470	11.2	4.8	140	24.5
OME933	14	495	485	11.2	4.8	140	24.5
OME934	14	510	500	10	4.0	180	31.5
OME935	14	420	410	9.8	4.1	180	31.5

cont.